



"F" TYPE COIL



DESCRIPTION

3/4 inch (19 mm) I.D. Coil.

Color identification: silver metallic envelope

FEATURES


One piece encapsulated design that is:

- Immersion proof
- No external metal shell
- Internal arc suppression diode available on request


COIL SPECIFICATION

Wattage	20 Watts Nominal
Duty Rating	Continuous Duty $\pm 10\%$ rated voltage at 120°F (49°C) ambient
Min Current for Actuation	80% of rated current at room temperature
Magnet Wire Class	H (200°C)
Heat insulation Class	H (180°C)
Ambient Temperature Range	-30° to 60°C
Protection degree	Up to IP 65 (with connector and suitable seals)
Encapsulation Material	Glass filled polyester, resistant to moisture, caustic solutions, fungus and vibration


FHC



FDI



FJT



ORDERING INFORMATION

F	-	-	-
TERMINATIONS			
DIN 43650 (Hirschmann)	HC	12	
AMP Junior Timer - Integral	JT	24	
Deutsch - Integral DT04-2P	DI		
			VOLTAGE
			12 VDC / 1.66 A
			24 VDC / 0.83 A

Approximate Coil Weight: .49 lbs (.22 kg)

WARNING: the specifications/application data shown in our catalogs and data sheets are intended only as a general guide for the product described (herein). Any specific application should not be undertaken without independent study, evaluation, and testing for suitability.